WAHATRANSCO Maharashtra State Electricity Transmission Co. Ltd.

MAHARASHTRA STATE ELECTRICITY TRANSMISSION COMPANY LTD (CIN NO- U40109MH2005SGC153646)

From,

Executive Engineer,

PAC Division, Karad,

Zone office premises,

At-Vijaynagar, Post - Supane.

Tal-Karad, Dist: Satara - 415 114.

Contact No.: 02164-255109

E-mail: - ee3510@mahatransco.in

Ref:- EE/PACD/KRD/T/ No.

1 5 6

Date: 3 1 JUL 2025

E- Enquiry (Budgetary offer)

Sub: - Enquiry for submission of <u>budgetary offer</u> for supply of Ferrule Printing Machine for various Testing units under PAC Division Karad.

Dear Sir

Budgetary offers are invited by the undersigned for supply of supply of Ferrule Printing Machine for various Testing units under PAC Division Karad. on or before: 07.08.2025 up to 17:00

Hrs. The other terms and conditions are as mentioned below.

- 1) Quotation should be duly filled in and submitted to this office via post or e-mail ee3510@mahatransco.in
- 2) This enquiry is solely for collection of offer for estimate purpose & not for work allocation.
- 3) The offer should be submitted as per details mentioned below.
- 4) Quote rate in prescribed format.

Particular	Unit	Rate per unit (Excl. Taxes)
"Ferrule Printing Machine with PC & manual operation having following specifications:	No.	
PRINTING METHOD Thermal Transfer Method (300dpi)		
DISPLAY LCD dot matrix: 64 x 160 Pixel (Backlit)		
PRINTING SPEED 40mm/s (Standard) 20mm/s (Low Temperature Mode)		
MAXIMUM PRINTING LENGTH Tube: 100m, Tape: 5m		
By multiple copy printing, maximum 30 copies, up to Tube : 100m, Tape : 7m		
MAXIMUM NUMBER OF CHARACTERS TO INPUT 5,000		Exercise Political

characters per file

CHARACTER SIZE 1.3, 2, 3, 4, 6mm height

USABLE TUBE

φ1.5mm - 8.0mm (PVC Tube)

φ2.0mm - 6.5mm (Heat Shrink Tube)

USABLE TAPE

Width 5, 9, 12mm (MAX genuine tape)

TUBE CUTTING METHOD

Auto half cut, manual full cut

INTERNAL MEMORY 250,000 characters (Maximum 50 files)

EXTERNAL MEMORY USB memory

INTERFACE USB 2.0 full speed

POWER SUPPLY DC12V, 4.2A Use only specified AC Adapter (100V - 240V) / 4 AA batteries

POWER CONSUMPTION MAX 40W

1) OPERATING ENVIRONMENT 50F to 95F (10°C to 35°C)"

Executive Engineer PAC Division Karad.