

MAHARASHTRA STATE ELECTRICITY TRANSMISSION COMPANY LTD (CIN NO- U40109MH2005SGC153646)

Office of the,

Executive Engineer

MSETCL EHV O&M, Division,

Near Market Yard, Bapat Camp, Kolhapur

Tal: - Karvir, Dist-Kolhapur-416 005,

E-mail: - ee3210@mahatransco.in

MSETCL/EE/EHV O&M/Dn./Kop/T/LP/ 1543



Date: 18.08.2025

E-Enquiry (Budgetary offer)

Sub: - Enquiry for submission of <u>budgetary offer</u> for supply and installation of LED lights at various substation under EHV O&M DN, Kolhapur.

Dear Sir,

Budgetary offer are invited by the undersigned for **supply and installation of LED lights at various substation** under EHV O&M DN, Kolhapur **on or before:25.08.2025 up to 15:00 Hrs**. The other terms and conditions are as mentioned below.

- 1) Quotation should be duly filled in and submitted to this office <u>via post or e-mail</u> <u>ee3210@mahatransco.in</u>
- 2) This enquiry is solely for collection of offer for estimate purpose & not for work allocation.
- 3) The offer should be submitted as per details mentioned below.
- 4) Quote rate in prescribed format & Attached Specifications:
- 5) Specification are as follows.

| Particulars | Qty | Rates Incl of labour cess, packaging and forwarding, transportation and GST |
|--|-----|---|
| Specification for supply of LED lights: | 268 | • |
| 1. Wattage - 200W | | |
| 2. LED luminaries efficency - 115 lm / W | | |
| 3. Luminious efficency - 9000 CD | | |
| 4. PF - 0.9 and above. | | |
| 5. CRI - > 70 | | |
| 6. External surge protection - >= 10kV. | | |
| 7. Internal surge protection - >= 4kV. | | |
| 8. Operating Voltage range - 110V to 270V | | |
| 9. Lumen - > 25000 lumen. | | |
| 10. Overvoltage protection - 310V | | |
| 11. Total harmonic distortion - <15% | | |
| 12. Correlated Colour temperature - 5700K +/ - 500K | | |
| 13. Operating temperature - 40 to 55 degrees celcius. | | |
| 14. Fixture - Single pressure die cast aluminum housing with fins | | |
| for better heat dissipation. Heat resistant through toughened glass | | |
| provided on fixture. | | |
| 15. Drivers - Short circuit protection and should be easily replaceable. | | |
| 16.Certification - BIS. | | |
| 17. Protetion - IP - 66 and dust proof. | | |
| 18. Mounting - formula array LED with pad size 60 X 66 mm. | | |
| 19. Warantee - Min 5 years. | | |
| 20. IS - 10322 for LED, 15885 for drivers | | |
| Warrantry Period: 5 Years. | | |

(Namdev Patil)
Executive Engineer
EHV O&M Dn. Kolhapur.