



MAHARASHTRA STATE ELECTRICITY TRANSMISSION CO. LTD.

Name of Office : 400kV R.S. O&M Dn. Karad.
Office Address : Administrative Building, Ground Floor, Vijaynagar,
Post – Supane, Tal – Karad Dist – Satara, Pin Code. 415114
Email ID : ee3130@mahatransco.in
Website : www.mahatransco.in.
CIN No. : U40109MH2005SGC153646

EE/400kV/RS/O&M/DN/KRD/T/No.

No 0 0 0 0 2'

Date: **1 JAN 2026**


E-ENQUIRY FOR BUDGETARY OFFER
(Through MSETCL web page)

TO WHOM SO EVER IT MAY CONCERN

BUDGETARY OFFER

Please find attached herewith a detail schedule for supply of grass cutter at 400kV Karad substation. All interested & experienced bidders are requested to submit their best lowest **budgetary offer** on the Mail ID: ee3130@mahatransco.in or submit physically to this office for the same up to **Dated. 08.01.2026 up to 18:00hrs.** Taxes should be quoted distinctly if any.

Please note that this budgetary offer is for estimation purpose only.


(C.L. Bharamgunde)
Executive Engineer,
400kV R.S.(O&M)Dn., Karad.



MAHARASHTRA STATE ELECTRICITY TRANSMISSION COMPANY LTD

400KV RS (O&M) Division, Karad
(CIN No.- U40109MH2005SGC153646)

SCHEDULE 'A'

Sub – Supply of grass cutter at 400kV Karad Substation.


Technical Specification Sheet:

Item: Petrol Operated Grass / Weed Cutter (Heavy Duty Type)

Sr. No.	Description	Specification / Requirement	Unit	Qty.	Remarks
1	Type	Portable, shoulder-mounted / backpack-type petrol-operated brush cutter , suitable for heavy-duty grass and weed cutting in open switchyard, roadside, and uneven terrain.	No.	As required	—
2	Engine Type	Air-cooled, single-cylinder, 2-stroke petrol engine	—	—	Heavy-duty continuous operation type
3	Engine Displacement	52cc (minimum)	—	—	High-power performance
4	Rated Power Output	1.9–2.0 HP (approx. 1.4–1.5kW)	—	—	—
5	Fuel Type	Unleaded petrol mixed with 2T oil (ratio 25:1 or as per manufacturer)	—	—	—
6	Fuel Tank Capacity	≥ 0.9litres	—	—	For longer runtime
7	Ignition System	CDI (Capacitor Discharge Ignition)	—	—	Reliable starting
8	Starting System	Recoil (manual) start	—	—	—
9	Transmission	Rigid or flexible drive shaft with heavy-duty gear head	—	—	—
10	Handle Type	“U” shape / bull-horn or loop handle with vibration damping	—	—	For operator comfort
11	Cutting Attachments	a) Nylon line trimmer head (for soft grass) b) 3-tooth or 4-tooth metal blade (for thick weeds) c) Optional circular saw blade (for dense shrubs)	Set	—	Interchangeable type
12	Weight (Dry)	≤ 10 kg (without fuel)	—	—	Light and portable
13	Accessories	Shoulder harness/belt, tool kit, spark plug wrench, safety guard, and extra nylon line	Set	—	Standard supply
14	Performance	Capable of continuous cutting for minimum 45 minutes per fuel tank	—	—	—
15	Noise Level	≤ 100 dB with muffler	—	—	—
16	Safety Standards	Conforming to IS/ISO 11806 or equivalent international standard for combustion-engine-driven brush cutters	—	—	—
17	Recommended Make / Model	STIHL FS 250 / Husqvarna 143R-II / Honda UMK 435T / Kisan Kraft KK-BC-8652 / Makita EBH341U or equivalent approved make	—	—	Equivalent models acceptable

NOTE :-

This budgetary offer is only for estimation purpose.


(C.L.Bharamgunde)

Executive Engineer,
400kV R.S.(O&M)Dn., Karad.

