

MAHARASHTRA STATE ELECTRICITY TRANSMISSION COMPANY LTD

From,
Executive Engineer
PAC Division, Near Market Yard,
Bapat Camp, Kolhapur-416005 Off:-0231-2662668
E-mail: - ee3530@mahatransco.in

No.EE/PAC/Kop/Tech/No. 33

Date:- 29.01.2026

E-Enquiry (Budgetary Offer)

Sub: - E-Enquiry for submission of Budgetary offer for Supply of Ferrule Printing machine under PAC Division Kolhapur.

Dear Sir,

The Budgetary offers are invited by undersigned for Supply of Ferrule Printing machine under PAC Division Kolhapur. The quotation giving full details of your terms and conditions for above work mentioning validity of the rate, should reach this office on or before **03.02.2026** at **18.00** hrs. You are requested to quote your reasonable rates with due consideration of the following points.

Terms and Conditions-

1. The rates quoted must be inclusive of all taxes and Calibration work will be done at office of the Executive Engineer, PAC Division, Kolhapur.
2. Quotation should be duly filled & submitted to this office via post or email - ee3530@mahatransco.in
3. The Enquiry is solely for collection of offer for estimation purpose & does not guarantee work allocation
4. The offer rate submitted should be valid for minimum one year period.

-sd-

Executive Engineer
PAC Division Kolhapur.

Schedule 'A'

Sub- Supply of Ferrule Printing machine under PAC Division Kolhapur.

Sr, No.	Details	Qty.	Unit Rate	GST 18 %/unit	Amt.
1	"Ferrule Printing Machine with PC & manual operation having following specifications: PRINTING METHOD Thermal Transfer Method (300dpi) DISPLAY LCD dot matrix: 64 x 160 Pixel (Backlit) PRINTING SPEED 40mm/s (Standard) 20mm/s (Low Temperature Mode) MAXIMUM PRINTING LENGTH Tube : 100m, Tape : 5m By multiple copy printing, maximum 30 copies, up to Tube : 100m, Tape : 7m MAXIMUM NUMBER OF CHARACTERS TO INPUT 5,000 characters per file CHARACTER SIZE 1.3, 2, 3, 4, 6mm height USABLE TUBE φ1.5mm - 8.0mm (PVC Tube) φ2.0mm - 6.5mm (Heat Shrink Tube) USABLE TAPE Width 5, 9, 12mm (MAX genuine tape) TUBE CUTTING METHOD Auto half cut, manual full cut INTERNAL MEMORY 250,000 characters (Maximum 50 files) EXTERNAL MEMORY USB memory INTERFACE USB 2.0 full speed POWER SUPPLY DC12V, 4.2A Use only specified AC Adapter (100V - 240V) / 4 AA batteries POWER CONSUMPTION MAX 40W OPERATING ENVIRONMENT 50F to 95F (10°C to 35°C)"	1			
	Total				

-sd-

**Executive Engineer
PAC Division Kolhapur**