MAHARASHTRA STATE ELECTRICITY TRANSMISSION CO. LTD. (CIN No.U40109MH2005SGC153646)

Office of the

Executive Engineer

400KV RS Division Khadka (MSETCL)

Khadka-Bhusawal, Pin-425201

Mobile No.7768001155

Phone No (02582) (O) 247308, (Control Room) 247 698 Fax No-(02582) 247 308

Email: ee5240@mahatransco.in

Web Site- www.mahatransco.in

Ref. No. EE/400KV/RS/Dn/KDK/BS 10 - 0 4 5 5

TO WHOM SO EVER IT MAY CONCERN

This office required the budgetary offer for the for Supply of New Safety Helmets, Safety Belts & Electrical Rubber Hand Gloves as per specifications & applicable IS standards at 400KV Receiving Station Division Khadka.

All interested bidders are requested to submit their best reasonable budgetary offer on Email ID:ee5240@mahatransco.in along with HSN code & applicable rate of GST for above material upto Dtd: 15.06.2019. The details of the materials are mentioned in schedule "A" Please note that this budgetary offer is for estimation purpose only.

Enclose: - Schedule "A"

Executive Engineer (Charge) 400 kV RS Dn, MSETCL, Khadka- Bhusawal.



Sr. No.	Particular of Materials	Specification	Unit	Qty.	Unit Rate
1	Safety Helmet	Industrial Safety Helmet (Ratchet Type) made of HDPE (Impact & UV Resistance) ISI approved confirming to IS 2925 and CE approved confirming to EN -397-1995. Four Point Head suspension with Brushed cloth and Sweat band with adjustable Chin Strap.	Nos.	48	Hand's street No.
	CIRCLES VIDE	Color Required –White-18, Yellow-30. The safety belt shall comply with I.S.3521-	-emphas a	O'LLLYN-1	
2	Dec Starrende	1989/1990 or latest version. Type: Class D (with Front Mounted D Ring) with Full Body support.	establică îi prestăță d punt boss		n suched privilegos)
	Safety Belts	MATERIALS: WEBBING: All belts and harnesses shall be made from leather materials. The material shall have a uniform thickness and uniform width. The waist belt, pole straps of safety belts and harnesses shall be made from nylon/ polyester webbing which shall not break under a minimum tensile load of 2000 KG. (19.6 KN). The test specimen shall be of entire cross section whose width and thickness should be 44 mm and 3 mm. THREADS FOR SEWING: Threading (Leather/nylon/polyester) for sewing load bearing components shall have similar	Nos.	15	Harracill (2 ft July) (2 ft July) (2 ft July) (3 ft July) (4 ft July) (5 ft July) (6 ft July) (7 ft July) (7 ft July) (8 ft July)
		physical and chemical properties to the materials being sewn. RIVETS AND WASHERS: All rivets and washers used for joining the various sections shall be made from copper.			
3	Hand Gloves ELECTRICAL HAND GLOVES	Electrical Rubber Hand gloves as per IS 4770 / 1991 without joint, having test Potential 33 KV 380 mm long and working potential is 33 KV. (Test certificate must be attached with delivery challan)	Pair	13	

(R.S.Patil)
Executive Engineer (Charge)
400 kV RS Dn, MSETCL,
Khadka- Bhusawal.